

January 5, 2004

Case No : US010726 (7790/69)

Serial No.: 10/037,490

Filed: December 28, 2001

Page 2 of 12

**CLAIM AMENDMENTS**

Claims 11-30 are currently pending in the application.

Please amend claims 11, 13-15, 18, 20, 22, 25, 27, and 29 as shown below for non-statutory purposes of obviating a claim objection of claims 18 and 22, and for clarifying the term "resonant impedance circuit" and "resonant impedance means" in claims 11, 13, 15, 18, 20.

The following listing of claims 1-30 will replace all prior versions, and listings, of claims in the application:

1.-10. (Cancelled)

11. (Currently Amended) A device, comprising:

a first LED array having a first anti-parallel configuration;

an inverter operable to provide an alternating voltage; and

a first resonant impedance circuit including a first resonant inductor and a first resonant capacitor connected to said first LED array in a first series resonant, series loaded configuration having said first resonant inductor connected in series to said inverter, and said first resonant capacitor connected in series between said first resonant inductor and said first LED array,

wherein said first resonant impedance circuit directs a first flow of a first alternating current through said first LED array in response to the alternating voltage having a first polarity and directs a second flow of the first alternating current through said first LED array in response to the alternating voltage having a second polarity.

12. (Previously Presented) The device of claim 11, wherein said first LED array includes at least one of a LED pair, a LED string and a LED matrix.

13. (Currently Amended) The device of claim 11,

further comprising a second LED array having a second anti-parallel configuration;

January 5, 2004  
Case No.: US010726 (7790/69)  
Serial No.: 10/037,490  
Filed: December 28, 2001  
Page 3 of 12

wherein said first resonant impedance circuit further includes a second resonant capacitor;

wherein said first resonant inductor and said second resonant capacitor are connected to said second LED array in a second series resonant, series loaded configuration having said first resonant inductor connected in series to said inverter, and said second resonant capacitor connected in series between said first resonant inductor and said second LED array; and

wherein said first resonant impedance circuit directs a third flow of a second alternating current through said second LED array in response to the alternating voltage having the first polarity and directs a fourth flow of the second alternating current through said second LED array in response to the alternating voltage having the second polarity.

14. (Currently Amended) The device of claim 11, further comprising:  
a second LED array having a second anti-parallel configuration; and  
a second resonant impedance circuit including a second resonant inductor and a second resonant capacitor connected to said second LED array in a second series resonant, series loaded configuration having said second resonant inductor connected in series to said inverter, and said second resonant capacitor connected in series between said second resonant inductor and said second LED array,

wherein said second resonant impedance circuit directs a third flow of a second alternating current through said second LED array in response to the alternating voltage having the first polarity and directs a fourth flow of the second alternating current through said second LED array in response to the alternating voltage having the second polarity.

15. (Currently Amended) A device, comprising:  
a first LED array having a first anti-parallel configuration;  
an inverter operable to provide an alternating voltage; and  
a first resonant impedance circuit including a first resonant inductor and a first resonant capacitor array connected to said first LED array in a first series resonant,

January 5, 2004

Case No.: US010726 (7790/69)

Serial No.: 10/037,490

Filed: December 28, 2001

Page 4 of 12

series loaded configuration having said first resonant inductor connected in series to said inverter, and said first resonant capacitor array connected in series between said first resonant inductor and said first LED array,

wherein said first resonant impedance circuit directs a first flow of a first alternating current through first LED array in response to the alternating voltage having a first polarity and directs a second flow of the first alternating current through said first LED array in response to the alternating voltage having a second polarity.

16. (Previously Presented) The device of claim 15, wherein said first LED array includes at least one of a LED pair, a LED string and a LED matrix.

17. (Previously Presented) The device of claim 15, wherein said first LED array includes a switch operable to control at least one of the first flow and the second flow of the first alternating current through said first LED array.

18. (Currently Amended) The device of claim 15,  
further comprising a second LED array having a second anti-parallel configuration;

wherein said first resonant impedance circuit further includes a second resonant capacitor array;

wherein said first resonant inductor and said second resonant capacitor array are connected to said second LED array in a second series resonant, series loaded configuration having said first resonant inductor connected in series to said inverter, and said second resonant capacitor array connected in series between said first resonant inductor and said second LED array; and

wherein said first resonant impedance circuit directs a third flow of a second alternating current through said second LED array in response to the alternating voltage having the first polarity and directs a fourth flow of the second alternating current through said second LED array in response to the alternating voltage having the second polarity.

January 5, 2004

Case No.: US010726 (7790/69)

Serial No.: 10/037,490

Filed: December 28, 2001

Page 5 of 12

19. (Previously Presented) The device of claim 18,  
wherein said first LED array includes a first switch operable to control at least one of the first flow and the second flow of the first alternating current through said first LED array; and  
wherein said second LED array includes a second switch operable to control at least one of the third flow and the fourth flow of the second alternating current through said second LED array.
20. (Currently Amended) The device of claim 15, further comprising:  
a second LED array having a second anti-parallel configuration; and  
a second resonant impedance circuit including a second resonant inductor and a second resonant capacitor array connected to said second LED array in a second series resonant, series loaded configuration having said second resonant inductor connected in series to said inverter, and said second resonant capacitor array connected in series between said second resonant inductor and said second LED array,  
wherein said second resonant impedance circuit directs a third flow of a second alternating current through said second LED array in response to the alternating voltage having the first polarity and directs a fourth flow of the second alternating current through said second LED array in response to the alternating voltage having the second polarity.
21. (Previously Presented) The device of claim 20,  
wherein said first LED array includes a first switch operable to control at least one of the first flow and the second flow of the first alternating current through said first LED array; and  
wherein said second LED array includes a second switch operable to control at least one of the third flow and the fourth flow of the second alternating current through said second LED array.
22. (Currently Amended) A device, comprising:

January 5, 2004

Case No.: US010726 (7790/69)

Serial No.: 10/037,490

Filed: December 28, 2001

Page 6 of 12

a first LED array having a first anti-parallel configuration;  
an inverter operable to provide an alternating voltage; and  
a first ~~resonating resonant~~ impedance circuit connected to said first LED array  
in a first series resonant, series loaded configuration having said first ~~resonating  
resonant~~ impedance circuit connected in series between said inverter and said first  
LED array,

wherein said first ~~resonating resonant~~ impedance circuit includes  
means for directing a first flow of a first alternating current through said first LED  
array in response to the alternating voltage having a first polarity and directing a  
second flow of the first alternating current through said first LED array in response to  
the alternating voltage having a second polarity.

23. (Previously Presented) The device of claim 22, wherein said first LED array  
includes at least one of a LED pair, a LED string and a LED matrix.

24. (Previously Presented) The device of claim 22, wherein said first LED array  
includes a switch operable to control at least one of the first flow and the second flow  
of the first alternating current through said first LED array.

25. (Currently Amended) The device of claim 22,  
further comprising a second LED array having a second anti-parallel  
configuration;  
wherein said first ~~resonating resonant~~ impedance circuit is connected to said  
second LED array in a second series resonant, series loaded configuration having said  
first ~~resonating resonant~~ impedance circuit connected in series between said inverter  
and said second LED array; and

wherein said first ~~resonating resonant~~ impedance circuit includes means for  
directing a third flow of a second alternating current through said second LED array  
in response to the alternating voltage having the first polarity and directing a fourth  
flow of the second alternating current through said second LED array in response to  
the alternating voltage having the second polarity.

January 5, 2004

Case No.: US010726 (7790/69)

Serial No.: 10/037,490

Filed: December 28, 2001

Page 7 of 12

26. (Previously Presented) The device of claim 25,

wherein said first LED array includes a first switch operable to control at least one of the first flow and the second flow of the first alternating current through said first LED array; and

wherein said second LED array includes a second switch operable to control at least one of the third flow and the fourth flow of the second alternating current through said second LED array.

27. (Currently Amended) The device of claim 22, further comprising:

a second LED array having a second anti-parallel configuration; and

a second ~~resonating~~ resonant impedance circuit connected to said second LED array in a second series resonant, series loaded configuration having said second ~~resonating~~ resonant impedance circuit connected in series between said inverter and said second LED array,

wherein said second ~~resonating~~ resonant impedance circuit includes means for directing third flow of a second alternating current through said second LED array in response to the alternating voltage having the first polarity and directing a fourth flow of the second alternating current through said second LED array in response to the alternating voltage having the second polarity.

28. (Previously Presented) The device of claim 27,

wherein said first LED array includes a first switch operable to control at least one of the first flow and the second flow of the first alternating current through said first LED array; and

wherein said second LED array includes a second switch operable to control at least one of the third flow and the fourth flow of the second alternating current through said second LED array.

29. (Currently Amended) A device, comprising:

at least one LED array, each LED array having an anti-parallel configuration;

January 5, 2004

Case No.: US010726 (7790/69)

Serial No.: 10/037,490

Filed: December 28, 2001

Page 8 of 12

an inverter means for providing an alternating voltage; and

a ~~resonating~~ resonant impedance means connected to each LED array in a series resonant, series loaded configuration having said ~~resonating~~ resonant impedance means connected in series between said inverter and each LED array, said ~~resonating~~ resonant impedance means for directing a first flow of a first alternating current through said at least one LED array in response to the alternating voltage having a first polarity and directing a second flow of the first alternating current through said at least one LED array in response to the alternating voltage having a second polarity.

30. (Previously Presented) The device of claim 29, wherein said at least one LED array includes switching means for controlling at least one of the first flow and the second flow of the first alternating current through said at least one LED array.